

NightViu® Driving Light M CB RO 3000

2801701009300



Product information

Order number	2801701009301
Application (Category and Product specific)	Additional main beam and position light

Electrical data

Nominal voltage	12/24 V
Nominal power	39 W (1 W)
Connector	DEUTSCH Female DT04-2P 2-Way receptacle

Photometric data

Luminous flux	3000 lm
Colour temperature	6000 K $\pm$ 500K
Light distance at 1lx	$\geq$ 300 m

LED module information

Number of LEDs per module	6/12
---------------------------	------

Weight

Kit	2300 g
-----	--------

Environmentalconditions

Ambient temperature	-30 °C to +60 °C
---------------------	------------------

Lifetime

Service life Tc L70B50 *)	> 5000 h
---------------------------	----------

*) By definition, the module is defect as soon as the luminous flux of 50% of the used LEDs drops below 70% of the specified minimum value

Certificates & Standards

Standards complied:	ECE R10, R112, R7
Certification marks - approval:	E4 approval
Type of protection:	IP69K



Scope of delivery

A diagram showing the components included in the scope of delivery: the headlight unit, a mounting bracket, several screws and bolts, and a cable.

Dimensions

A diagram showing the dimensions of the headlight unit. The width is 109mm, the height is 201mm, and the diameter of the mounting bracket is ø176mm. The unit is shown from three different angles: front, side, and rear.

