

NightViu® Driving Light M CB RE 4000

2801701011300



Product information

| | |
|---|---|
| Order number | 2801701011301 |
| Application (Category and Product specific) | Additional main beam and position light |

Electrical data

| | |
|-----------------|---|
| Nominal voltage | 12/24 V |
| Nominal power | 70 W (1.5 W) |
| Connector | DEUTSCH Female DT04-2P 2-Way receptacle |

Photometric data

| | |
|-----------------------|-------------------|
| Luminous flux | 4000 lm |
| Colour temperature | 6000 K \pm 500K |
| Light distance at 1lx | \geq 430 m |

LED module information

| | |
|---------------------------|---------|
| Number of LEDs per module | 10 / 16 |
|---------------------------|---------|

Weight

| | |
|-----|--------|
| Kit | 3380 g |
|-----|--------|

Environmental conditions

| | |
|---------------------|------------------|
| Ambient temperature | -30 °C to +60 °C |
|---------------------|------------------|

Lifetime

| | |
|---------------------------|----------|
| Service life Tc L70B50 *) | > 5000 h |
|---------------------------|----------|

*) By definition, the module is defect as soon as the luminous flux of 50% of the used LEDs drops below 70% of the specified minimum value

Certificates & Standards

| | |
|---------------------------------|-------------------|
| Standards complied: | ECE R10, R112, R7 |
| Certification marks - approval: | E4 approval |
| Type of protection: | IP69K |

